Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended): A data processing device using pipeline control, comprising:

an instruction queue in which a plurality of instruction codes are fetched;

a fetch address operation circuit which calculates a fetch address used to fetch an instruction code in the instruction queue;

a fetch circuit which fetches an instruction code that is read out based on the fetch address into the instruction queue; and

a branch information setting circuit which decodes a branch setting instruction instruction, which wherein the branch setting instruction explicitly or implicitly implies information for specifying specifies a branch address and a branch target address address, when the fetch address is a the branch address after x-th instruction from the branch setting instruction, the branch information setting circuit stores the branch address in a branch address storage register and the branch target address in a branch target address storage register, when the branch setting instruction is decoded,

wherein the fetch address operation circuit includes a circuit which compares one of a previous fetch address and an expected next fetch address with a value stored in the branch address storage register, and then determines whether or not to output a value stored in the branch target address storage register as a next fetch address, based on the comparison result.

Appl. No. 10/601,005 Amdt. Dated September 15, 2006 Reply to Final Office Action of May 15, 2006

2. (Currently amended): A data processing device using pipeline control, comprising:

an instruction queue in which a plurality of instruction codes are fetched;

a fetch address operation circuit which calculates a fetch address used to fetch an instruction code in the instruction queue;

a fetch circuit which fetches an instruction code that is read out based on the fetch address into the instruction queue; and

a branch information setting circuit which decodes a branch setting instruction instruction, which wherein the branch setting instruction explicitly or implicitly implies information for specifying specifies a branch address and a branch target address address, when the fetch address is a the branch address after x-th instruction from the branch setting instruction, the branch information setting circuit stores the branch address in a branch address storage register and the branch target address in a branch target address storage register, when the branch setting instruction is decoded,

wherein the fetch address operation circuit includes a circuit which compares an expected next fetch address obtained by incrementing a value in a fetch program counter by one instruction length with a value stored in the branch address storage register, and then outputs a value stored in the branch target address storage register as a next fetch address when the expected next fetch address coincides with the value in the branch address storage register, or outputs the expected next fetch address as a next fetch address when the expected next fetch address does not coincide with the value in the branch address storage register.

3. (Original): The data processing device as defined in claim 1, wherein: the branch setting instruction includes a loop instruction which designates a loop count;

the branch information setting circuit decodes the loop instruction which instructs to repeat a branch to the branch target address the number of times equal to the loop count, and stores the loop count designated by the loop instruction; and

the fetch address operation circuit includes a circuit which outputs a value stored in the branch target address storage register as a next fetch address until the number of times the branch to the branch target address repeats reaches the loop count.

4. (Original): The data processing device as defined in claim 2, wherein: the branch setting instruction includes a loop instruction which designates a loop count;

the branch information setting circuit decodes the loop instruction which instructs to repeat a branch to the branch target address the number of times equal to the loop count, and stores the loop count designated by the loop instruction; and

the fetch address operation circuit includes a circuit which outputs a value stored in the branch target address storage register as a next fetch address until the number of times the branch to the branch target address repeats reaches the loop count.

5. (Original): The data processing device as defined in claim 1, wherein: the branch setting instruction includes a loop instruction which designates a loop count;

the branch information setting circuit decodes the loop instruction which instructs to repeat a branch to the branch target address the number of times equal to the loop count, and stores the loop count designated by the loop instruction; and

the fetch address operation circuit includes a circuit which decrements a value set in the loop counter each time when a branch to the branch target address occurs, and outputs a value obtained by incrementing the branch address by one instruction length as a next fetch address when the value of the loop counter reaches zero.

6. (Original): The data processing device as defined in claim 2, wherein: the branch setting instruction includes a loop instruction which designates a loop count;

the branch information setting circuit decodes the loop instruction which instructs to repeat a branch to the branch target address the number of times equal to the loop count, and stores the loop count designated by the loop instruction; and

the fetch address operation circuit includes a circuit which decrements a value set in the loop counter each time when a branch to the branch target address occurs, and outputs a value obtained by incrementing the branch address by one instruction length as a next fetch address when the value of the loop counter reaches zero.

7. (Original): The data processing device as defined in claim 3, wherein: the branch setting instruction includes a loop instruction which designates a loop count;

the branch information setting circuit decodes the loop instruction which instructs to repeat a branch to the branch target address the number of times

equal to the loop count, and stores the loop count designated by the loop instruction; and

the fetch address operation circuit includes a circuit which decrements a value set in the loop counter each time when a branch to the branch target address occurs, and outputs a value obtained by incrementing the branch address by one instruction length as a next fetch address when the value of the loop counter reaches zero.

8. (Original): The data processing device as defined in claim 4, wherein: the branch setting instruction includes a loop instruction which designates a loop count;

the branch information setting circuit decodes the loop instruction which instructs to repeat a branch to the branch target address the number of times equal to the loop count, and stores the loop count designated by the loop instruction; and

the fetch address operation circuit includes a circuit which decrements a value set in the loop counter each time when a branch to the branch target address occurs, and outputs a value obtained by incrementing the branch address by one instruction length as a next fetch address when the value of the loop counter reaches zero.

9. (Original): The data processing device as defined in claim 3, wherein: the loop instruction has the branch target address which is fixed relative to the loop instruction and also has no branch target address information in an operand; and

the branch information setting circuit includes a circuit which calculates the value fixed relative to the loop instruction and stores the calculated value in the branch target address storage register.

Appl. No. 10/601,005 Amdt. Dated September 15, 2006 Reply to Final Office Action of May 15, 2006

10. (Original): The data processing device as defined in claim 4, wherein:
the loop instruction has the branch target address which is fixed
relative to the loop instruction and also has no branch target address information in
an operand; and

the branch information setting circuit includes a circuit which calculates the value fixed relative to the loop instruction and stores the calculated value in the branch target address storage register.

11. Original): The data processing device as defined in claim 5, wherein:
the loop instruction has the branch target address which is fixed
relative to the loop instruction and also has no branch target address information in
an operand; and

the branch information setting circuit includes a circuit which calculates the value fixed relative to the loop instruction and stores the calculated value in the branch target address storage register.

12. (Original): The data processing device as defined in claim 6, wherein: the loop instruction has the branch target address which is fixed relative to the loop instruction and also has no branch target address information in an operand; and

the branch information setting circuit includes a circuit which calculates the value fixed relative to the loop instruction and stores the calculated value in the branch target address storage register.

13. (Original): Electronic equipment comprising:

the data processing device as defined in claim 1;

means for receiving input data; and

means for outputting a result of processing the input data by the data

processing device.

Attorney Docket No. 81751.0061 Customer No. 26021

- 14. (Original): Electronic equipment comprising:
 the data processing device as defined in claim 2;
 means for receiving input data; and
 means for outputting a result of processing the input data by the data
 processing device.
- 15. (Original): Electronic equipment comprising:
 the data processing device as defined in claim 3;
 means for receiving input data; and
 means for outputting a result of processing the input data by the data
 processing device.
- 16. (Original): Electronic equipment comprising:
 the data processing device as defined in claim 4;
 means for receiving input data; and
 means for outputting a result of processing the input data by the data
 processing device.
- 17. (Original): Electronic equipment comprising:
 the data processing device as defined in claim 5;
 means for receiving input data; and
 means for outputting a result of processing the input data by the data
 processing device.
- 18. (Original): Electronic equipment comprising:
 the data processing device as defined in claim 6;
 means for receiving input data; and
 means for outputting a result of processing the input data by the data
 processing device.